









SYNTHETIC "NON-DRIP" GEL LUBRICANT FOR TUBE BENDING AND FORMING

PICODRAW 4030 GEL is a value-enhanced, synthetic lubricant that provides maximum barrier lubrication (improved lubricity) and film forming technologies for light to heavy-duty bending and forming of steel, stainless steel, aluminized tubes and pipes of all sizes.

PICODRAW 4030 GEL is an environmentally friendly and biodegradable formula offering several immediate benefits to replace conventional oil, oil-containing, or pigmented lubricants.

-  Non-flammable to eliminate fire and smoke hazards from in-process welding and improve environmental health and safety in plant operations.
-  Provides excellent stability and surface wetting characteristics to help cool parts and not squeeze out or flow off of surfaces.
-  Lowers product consumption through its "non-drip, stay-put" feature (less nozzle seepage) and eliminates excess waste.
-  Does not leave a build-up on surfaces and is easily removed with water to eliminate maintenance and post-process cleaning issues.
-  Helps eliminate galling, improves production performance, part quality, and secondary operations for tube and pipe makers and fabricators.
-  Does not contain oil and does not usually need to be cleaned off before welding (has no adverse effect to atmosphere) or component assembly.



PICODRAW 4030 GEL improves operator morale with its user-friendly, modern technology attributes.

PICODRAW 4030 GEL offers a positive return on assets through enhanced production performance, extended mandrel tool life, and excellent corrosion protection.

PICODRAW 4030 GEL is available in pails, drums, totes, and bulk.

PICO Chemical Corporation is an ISO 9001:2008 certified manufacturer of value-enhanced specialty chemicals and lubricants to clean, condition, lubricate, protect and provide value for metalworking applications and their related processes since 1976.

1-31-11



WORKHORSE PRODUCTS
SINCE 1976

Pico Chemical Corporation

Phone 708 757-4910 • Fax 708 757-4940

e-mail info@picochemical.com • www.picochemical.com

The description, statements and recommended use of this product are guidelines and may vary due to minor changes in formulation or manufacture, as to the date of printing. Because the use of this product is beyond the control of PICO Chemical Corporation, we assume no liability for incidental, consequential, or direct damages regardless of cause.

ISO
9001:2008
Certified