



PICO GUARD

RUST AND CORROSION INHIBITORS

PICO GUARD INHIBITORS HELP ELIMINATE COSTLY REJECTS, DOWN GRADING, REWORKING OR SCRAPPING VALUABLE INVENTORY CAUSED BY RUST AND CORROSION.

PICO GUARD INHIBITORS INCREASE PRODUCTIVITY, PROFITABILITY AND CUSTOMER CONFIDENCE.

PRODUCT	APPLICATION	DESCRIPTION
PICO GUARD 6200 Oil-based	Spray / immerse on surfaces to 300°F (149°C) . Water-emulsifiable	Dilutes with water. Up to 25%. Short-term indoor protection.
PICO GUARD 6205 Solvent-based	Spray / immerse on surfaces to 140°F (60°C) . Use for rolling / machining or warehouse storage. Water-displacing, non-discernible film.	Use as received. Short-term indoor protection.
PICO GUARD 6210 Solvent-based	Spray / immerse on surfaces to 140°F (60°C) . Use for rolling / machining or warehouse storage. Water-displacing, non-discernible film.	Use as received. Long-term indoor protection.
PICO GUARD 6222 Oil-based	Spray / immerse on surfaces to 140°F (60°C) . Use for rolling / machining or warehouse storage. Water-displacing, non-discernible film. Acid atmosphere protection.	Use as received. Indoor / under cover and limited outdoor protection.
PICO GUARD 6230 Solvent-based	Spray / immerse / brush / roll on surfaces to 30°- 140°F (-1° -60°C) for extended protection. Semi-viscous, firm transparent film, self-healing film	Use as received. Long-term indoor / outdoor protection.
PICO GUARD 6233 Oil-based	Spray / immerse on surfaces to 200°F (93°C) . Use for rolling / machining or warehouse storage. Water-displacing, non-discernible, light, oily film.	Use as received. Short-term indoor / outdoor protection.
PICO GUARD 6252 Solvent-based	Spray / immerse on surfaces to 140°F (60°C) . Use for rolling / machining or warehouse storage. Water displacing. Acid atmosphere protection.	Use as received. Indoor / under cover and limited outdoor protection.
PICO GUARD 17625 Synthetic Water-based	Spray / immerse on surfaces from 32°- 200°F (0° - 93°C) . Hard water tolerant. Clear, dry film.	Use as received. Short-term indoor protection.
PICO GUARD 17642 Synthetic Water-based	Spray / immerse / roll on surfaces from 32°- 200°F (0° - 93°C) . Hard water tolerant. Salt spray resistance. Clear, non-VOC, hydrophobic dry film.	Use as received. Long-term indoor / outdoor protection.
PICO GUARD OFI Oil-based Anti-seize lubricant	Spray / brush / flow on steel pipe threads, couplings, connectors, etc. Excellent for oil field and underground applications.	Use as received. Long-term indoor / outdoor protection.
PICO GUARD R 39-87 Steel Plate Rust preventive	Airless / air-assisted spray on / roll coat / brush-on. Substrate temperatures between 50°- 200°F (10° - 104°C) .	Use as received. Long-term indoor / outdoor protection.
PICO GUARD 40 Multi-purpose Lubricant	Spray / immerse on surfaces to 140°F (60°C) . Penetrates and removes light surface rust. Displaces water.	Use as received. Short-term indoor protection.
RPO Rust penetrating oil	Spray / immerse on surfaces to 140°F (60°C) . Penetrates Surface rust. Displaces water.	Use as received. Short-term indoor protection.

6-5-24 picoguardserieslc



PICO Chemical Corporation

Phone 708-757-4910 • Email: info@picochemical.com

www.picochemical.com

The description, statements and recommended use of this product are guidelines and may vary due to minor changes in formulation or manufacture, as to the date of printing. Because the use of this product is beyond the control of PICO Chemical Corporation, we assume no liability for incidental, consequential, or direct damages regardless of cause.

ISO
9001
Certified