

PICOCLEAN WTC

Plasma, Oxy and Waterjet Table Cleaner

GENERAL DESCRIPTION:



A multipurpose, environmentally friendly cleaner designed for use when cleaning plasma, oxy, and waterjet tables from long-term use or contamination.



Outstanding cleaning performance works thoroughly to flush and clean dirt, tramp oils, bacteria and odors, and other contaminants from tanks and equipment.



May be added to water table fluids prior to general cleaning and recharging with fresh PICO QUENCH GUARD products.



Can also be used to clean machine exteriors and parts.



Does not contribute to redeposition of soils, staining, or corrosion in machine coolants or systems.



PRODUCT FEATURES AND BENEFITS:

- | | |
|-----------------------|---|
| • Fast acting | • Non-flammable |
| • Low foaming | • Removes contamination |
| • Eliminates odors | • Cleans at ambient temperatures |
| • Multifunctional use | • Cuts grease, oil and dirt residue quickly |

Note: Can be added directly into current fluids from 2 to 10% PICOCLEAN WTC in fresh water, depending upon degree of system condition, and circulated from 4 to 24 hours before the system is scheduled to be thoroughly cleaned, dumped, and recharged; or if the system has been drained prior, a minimum of 5% WTC should be added directly into fresh water to start cleaning process.

For sump cleaning, review PICO Metalworking Fluid System Cleanout Procedure.

When making dilutions, always add concentrate to water or existing solution.

